



Eska[®]board

A three-layer laminated solid board, made of 100% recycled paper.
Lays flat, stays flat.

**Our solid board comes with a clear promise - it lays flat and stays flat;
even when it has been processed into end products.**

**We achieve this by using our own lining paper, monitoring the production process properly
and producing under the correct humidity levels.**

Flat is flat with Eska[®]board.



TECHNICAL PROPERTIES (INDICATION)

PRODUCT	CALIPER	GRAMMAGE	DYNAMIC STIFFNESS		BURSTING STRENGTH		COBB60	
	According to ISO 534	According to ISO 536	According to ISO 5629		According to ISO 2759		According to ISO 535	
	mm	g/m ²	MD mNm	CD mNm	top kPa	bottom kPa	max top g/m ² /60sec	max bottom g/m ² /60sec
UNLINED	1.00	630	170	90	540	540		
LINED	1.25	790	500	210	845	845		
	1.40	880	660	290	885	885		
	1.50	945	785	350	920	920		
	1.75	1105	1175	530	1005	1005		
	1.90	1195	1450	665	1060	1060		
	2.00	1260	1655	765	1100	1100		
	2.10	1325	1880	875	1145	1145		
	2.25	1420	2240	1060	1210	1210		
	2.40	1510	2635	1265	1285	1285		
	2.50	1575	2920	1415	1335	1335		
	2.75	1735	3700	1835	1470	1470		
	3.00	1890	4575	2330	1615	1615		
	3.25	2050	5900	2860	1800	1800		
	3.50	2205	7230	3525	2000	2000		
	3.75	2365	8270	3950	2085	2085		
	4.00	2520	9810	4900	2240	2240		

	SPECIFICATIONS	UNITS	TOLERANCES		TEST METHODS
CALIPER	See above	mm	< 1.5 mm ≥ 1.5 mm	± 0.05 mm (pallet average) ± 3% (pallet average)	ISO 534
SIZE		mm	Sheets Rotary cut Die cut	± 1 mm ± 0.25 mm ± 0.2 mm	
FLATNESS	0	%	Convex Concave S-shape	CD max. 1.5% MD max. 1.0% CD max. 1.0% MD max. 1.0% CD - sheets < 1 m. max. 3 mm - sheets ≥ 1 m. max. 5 mm MD max. 3 mm	Eska
MOISTURE CONTENT	7.0% abs.	%	-1.5% / +1.0%	(pallet average)	ISO 287

PRODUCT CERTIFICATES

- FSC® recycled 100% (CU-COC-809179)
- 100% PEFC (CU-PEFC-809179)
- Blue Angel The German Ecolabel (RAL)
- EN-71-part 3, Migration of certain elements (Toy Safety)
- Foodstuffs and Consumer Act (Food Safety)

SIZES

- Large sheets are available in any size from 500 x 500 mm to 1200 x 1600 mm
- Rotary cut sizes are available in any size from 100 x 150 mm to 480 x 1360 mm
- Die cut sizes are available in any size from 100 x 150 mm to 720 x 1050 mm

CERTIFICATE

CERTIFICATE N°: C809179FSC-COC-01.2008
CERTIFICATION CODE: CU-COC-809179

Field of attention:

FSC
Chain of Custody (COC)

Issued to:

Eska Graphic Board
Sappemeer, NETHERLANDS
Project in: NETHERLANDS


Standard:

FSC-STD-40-004 V2-0 FSC Standard for Chain of Custody Certification

Valid until: 11 March 2013

Control Union Certifications declares to have inspected the unit(s), and/or product(s) of the above mentioned client, and have found them in accordance with the standards mentioned above.
This certificate covers the unit(s), and/or product(s) as mentioned in the authenticated annex of this certificate.
This certificate is in force until further notice, provided that the above-mentioned client continues meeting the conditions as laid down in the client contract with Control Union Certifications.
Based on the annual inspections that Control Union Certifications performs, this certificate is updated and kept into force.

Date of certification:
13 March 2008
Place and date of issue:
Zwolle, 13 March 2008



FSC
ACCREDITED
FSC-ACC-019

FSC Trademark © 1996
Forest Stewardship Council A.C.

Declared by:

On behalf of the Managing Director

Mr. J.G. De Jong
Certifier

Control Union Certifications
P.O. Box 161
8000 AD Zwolle
The Netherlands
<http://www.controlunion.com>
tel.: +31(0)38-4260100